

## SECTION 1 - IDENTIFICATION OF CHEMICAL PRODUCT AND COMPANY

Oakgem Nominees Pty Ltd, trading as Bebrite  
Unit 5/4 Narabang Way  
Belrose NSW 2085

Phone: 1300 131 664  
Fax: 02 9450 2844

**Trade Name:** Penetrating Sealer  
**Substance:** Resin in xylene solution.  
**Product Use:** Tile sealing preparation.  
**Creation Date:** June, 2008  
**Revision Date:** June, 2008

## SECTION 2 - HAZARDS IDENTIFICATION

### Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. N, Dangerous to the environment. F, Flammable. Hazardous according to the criteria of ASCC.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R10, R38, R52, R65, R20/21/22. Flammable. Irritating to skin. Harmful to aquatic organisms.

Harmful: May cause lung damage if swallowed. Harmful by inhalation, in contact with skin, and if swallowed.

**Safety Phrases:** S2, S16, S23, S36, S38, S45, S46, S24/25. Keep out of reach of children. Keep away from sources of ignition - No smoking. Do not breathe vapours or mists. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately (show this MSDS where possible). If swallowed, contact a doctor or Poisons Information Centre immediately and show this MSDS or label. Avoid contact with skin and eyes.

**SUSDP Classification:** S5

**ADG Classification:** Class 3: Flammable liquids.

**UN Number:** 1866, RESIN SOLUTION, flammable

## Emergency Overview

**Physical Description & colour:** Clear colourless liquid.

**Odour:** Strong xylene odour.

**Major Health Hazards:** harmful by inhalation, in contact with skin, and if swallowed, skin irritant, if aspirated, may cause lung damage.

## Potential Health Effects

### Inhalation:

**Short term exposure:** Available data shows that this product is harmful, but symptoms are not available. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term inhalation.

### Skin Contact:

**Short term exposure:** Available data shows that this product is harmful, but symptoms are not available. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term exposure:** No data for health effects associated with long term skin exposure.

### Eye Contact:

**Short term exposure:** This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short term exposure:** Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

## MATERIAL SAFETY DATA SHEET

**Long Term exposure:** No data for health effects associated with long term ingestion.

**Carcinogen Status:**

**ASCC:** No significant ingredient is classified as carcinogenic by ASCC.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** No significant ingredient is classified as carcinogenic by IARC.

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Xylene	108-38-3	>30<50	350	655
Liquid hydrocarbon		30-60	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The ASCC TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### SECTION 4 - FIRST AID MEASURES

**General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

**Inhalation:** If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

### SECTION 5 - FIRE FIGHTING MEASURES

**Fire and Explosion Hazards:** This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Suitable extinguishing media are carbon dioxide, dry chemical, foam, water fog. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** Not available

**Upper Flammability Limit:** 7.0

**Lower Flammability Limit:** 1.1 (xylene)

**Autoignition temperature:** No data.

### MATERIAL SAFETY DATA SHEET

Flammability Class:

Flammable

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

## SECTION 7 - HANDLING AND STORAGE

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 10000kg or L of Dangerous Goods of Packaging Group III, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

ASCC Exposure limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Xylene	350	655

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: polyvinyl alcohol, Teflon, PE/EVAL.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

<b>Physical Description &amp; colour:</b>	Clear colourless liquid.
<b>Odour:</b>	Strong xylene odour.
<b>Boiling Point:</b>	Approx 140°C at 100kPa
<b>Freezing/Melting Point:</b>	Below 0°C.
<b>Volatiles:</b>	No specific data. Expected to be low at 100°C.
<b>Vapour Pressure:</b>	No data.
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	No data.
<b>Water Solubility:</b>	Negligible.
<b>pH:</b>	No data.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.

### MATERIAL SAFETY DATA SHEET

**Coeff Oil/water distribution:** No data  
**Autoignition temp:** No data.

## SECTION 10 - STABILITY AND REACTIVITY

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** strong acids, strong bases, oxidising agents.

**Fire Decomposition:** Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## SECTION 11 - TOXICOLOGICAL INFORMATION

**Local Effects:**

**Target Organs:** There is no data to hand indicating any particular target organs.

**Local Effects:**

**Target Organs:** There is no data to hand indicating any particular target organs.

Symptoms of significant exposure include dermatitis, eczema, eye irritation, and respiratory irritation.

Inhalation of xylene vapours can cause dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia and paresthesia of the hands and feet.

Xylene is narcotic at high concentrations.

## Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Xylene	Conc>=20%: Xn; R20/21; R38
Liquid Hydrocarbon	Conc>=10%: Xn; R65

## SECTION 12 - ECOLOGICAL INFORMATION

This product is harmful to aquatic organisms. Insufficient data to be further sure of status.

## SECTION 13 - DISPOSAL CONSIDERATIONS

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

## SECTION 14 - TRANSPORT INFORMATION

**ADG Code:** 1866, RESIN SOLUTION, flammable

**Hazchem Code:** 3Y

**Special Provisions:** 223

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

**Dangerous Goods Class:** Class 3: Flammable liquids.

**Packaging Group:** III

**Packaging Method:** P001, IBC03, LP01

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1

## MATERIAL SAFETY DATA SHEET

(Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

### **SECTION 15 - REGULATORY INFORMATION**

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredients: Xylene, Liquid hydrocarbon, are mentioned in the SUSDP.

### **SECTION 16 - OTHER INFORMATION**

**This MSDS contains only safety-related information. For other data see product literature.**

#### **Acronyms:**

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>ASCC</b>	Office of the Australian Safety and Compensation Council
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons
<b>UN Number</b>	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the ASCC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Copyright © Kilford & Kilford Pty Ltd, June, 2008.

<http://www.kilford.com.au> Phone (02)9251 4532

### **MATERIAL SAFETY DATA SHEET**